

Product Parameter

Operation Parameter			
A	Maximum overall height	mm	4020
B	Height to hinge pin	mm	3123
C	Height to top of cab	mm	2068
D	Height to bottom of level bucket	mm	2948
E	Length without standard bucket	mm	2958
F	Length with sandard bucket	mm	3727
G	Maximum dump angle	°	43
H	Dump height	mm	2395
J	Dump reach	mm	625
K	Rolback angle (bucket on ground)	°	30
L	Rolback angle at maximum height	°	93
M	Wheelbase	mm	1148
P	Ground	mm	205
Q	Departure angle	°	26
R	Turning radius from center (Coupler)	mm	1344
S	Turning radius from center (Bucket)	mm	2201
T	Turning radius from center (Machine rear)	mm	1747
U	Bumper overhang behind rear axle	mm	1170
V	Width over tire	mm	1475
W	Bucket width	mm	1830
Performance			
Operating weight	kg		3450
Rated operating capacity	kg		1100
Tipping load	kg		2000
Breakout force curl	kg		2480
Breakout force lift	kg		2430
Travel speed	km/h		12.6
Engine			
Brand			KUBOTA
Model			V3307DI-T
Type			4-cylinder, water cooling, diesel engine
Emission level			EPA Tier4 / EU Stage III A
Power	kW/rpm		55.4/2600
Peak torque	N·m/rpm		265/1600
Electrical System			
Starter	V/kW		12/3.0
Alternator rating	V/A		12/80
Battery	Ah		120
Service Refill Capalties			
Hydraulic tank	L		60
Fuel tank	L		110
Hydraulic System			
Hydraulic flow_standard	L/min		86
Hydraulic flow_high flow	L/min		131
Standard flow pressure	bar		210
High flow pressure	bar		165

Worldwide Network for Sales and Service

