

Equipment

The standard and optional equipment varies from country to country. For more information, please contact with us.

Engine		Cab	
Engine oil filter	●	AM/FM radio	●
Fuel filter	●	Cup holder	●
Oil-water separator	●	Floating shock absorber seat	●
Air filter	●	Air conditioner	●
Radiator	●	Engine safety start system	●
Alternator	●	Safety belt	●
Auxiliary water tank	●	FOPS/TOPS cab	●
Electronic fuel feed pump	●	FOPS/TOPS canopy	○
Muffler	●	Windscreen washer and wiper	●
Hydraulic system		Left/right rearview mirror	●
Hydraulic pilot control rod	●	Lighter	●
Slewing parking brake system	●	Safety device of front windscreen	○
Traveling parking brake system	●	Working devices	
Dual-speed traveling system	●	300 mm bucket	○
		680 mm bucket	●
Electro-hydraulic proportional handle (left)	○	1,500 mm bucket	○
Boom explosion-proof valve	●	1,600 mm arm	●
Arm explosion-proof valve	●	1,850 mm long rod	○
Dozer blade explosion-proof valve	○	Breaker pipeline	●
Operating mode switching valve	○	Auxiliary pipeline	●
Light		Mechanical quick change device	○
Boom light	●	Track	
Front cab light	●	400 mm rubber track	●
Warning light	●	400 mm steel track	○

● Standard equipment ○ Optional equipment

SWE60UF Technical Parameters			
Overall dimension (L × W × H)		mm	5500X1980X2550
Dimensions	A Length to center of rollers	mm	1965
	B Total track length	mm	2490
	C Ground clearance of platform	mm	640
	D Platform tail slewing radius	mm	1050
	E Chassis width	mm	1980
	F Track width	mm	400
	G Chassis clearance from the ground	mm	330
	H Track height	mm	575
	I Total length	mm	5500
	J Cab roof height	mm	2550
	K Upper-carriage width	mm	1845
Working range	a Max. cutting height	mm	5610
	b Max. unloading height	mm	3950
	c Max. digging depth	mm	3710
	d Max. vertical digging depth	mm	3199
	e Max. digging reach	mm	6235
	f Max. digging reach at ground level	mm	6105
	g Max. lift height of the dozer blade	mm	445
	h Max. digging depth of the dozer blade	mm	400
	i Swing radius (min.)	mm	2475
	Dozer blade length × width	mm	1960X390
Machine weight	with rubber track	kg	5700
	with steel track	kg	5770
Standard bucket capacity		m3	0.18
Digging force (bucket) (ISO)		kN	46.8
Digging force (arm) (ISO)		kN	31.1
Maximum traction force		kN	49
Slew angle (boom)		°	R50/L70
Traveling speed (Max/Min)		km/h	4.07/2.43
Gradeability		°	35
Ground pressure		kPa	33.87
Swing speed		rpm	9.4
Engine	Brand	KUBOTA	
	Model	V2607-DI-T-ET21	
	Type	4-cylinder and 4-stroke water cooling	
	Displacement	L	2.615
	Power/speed (gross/net)	kW/rpm	36.5/2000 36/2000
	Fuel tank capacity	L	70
Primary pump	Type	2 variable plunger pumps and 1 gear	
	Displacement	L/min	2x59+42
	Pressure of main relief valve	MPa	2×24.5+21
Hydraulic tank capacity		L	70

Load Capacity:

Lift Point Height	Lift Point Radius(MAX)		Lift Point Radius(5.0m)		Lift Point Radius(4.0m)		Lift Point Radius(3.0m)	
	Over-front(kg)	Over-side(kg)	Over-front(kg)	Over-side(kg)	Over-front(kg)	Over-side(kg)	Over-front(kg)	Over-side(kg)
4.0	915.0*	832.5*	—	—	—	—	—	—
3.0	765.0*	675.0*	—	—	1080.0*	937.5*	—	—
2.0	705.0*	577.5*	753.8*	637.5*	1125.0*	930.0*	1590.0*	1402.0*
1.0	675.0*	547.5*	682.5*	607.5*	855.0*	847.5*	1290.0*	1290.0*
0.0	622.5*	540.0*	630.0*	577.5*	907.5*	780.0*	1350.0*	1125.0*
-1.0	682.5*	600.0*	—	—	862.5*	735.0*	1267.5*	1065.0*
-2.0	795.0*	727.5*	—	—	855.0*	750.0*	1140.0*	990.0*

- Notes:
- 1、Load with * is limited by hydraulic capacity and based on ISO 10567.Rated loads do not exceed 87% of hydraulic capacity.
 - 2、Load without * is limited by tipping load and based on ISO 10567.Rated loads do not exceed 75% of tipping capacity.
 - 3、The excavator bucket,hook,sling and other lifting accessories are not included in this table.

